



## Contact Us

Office : 256.776.7786

Email : [sales@firetruckmall.com](mailto:sales@firetruckmall.com)

Website: [www.firetruckmall.com](http://www.firetruckmall.com)

15410 US Highway 231,

Union Grove, AL 35175

Stock #: 09919

Price: Sold and Delivered

2012 Helie International 2000 Gallon Tanker

○ 2012 Helie International 2000 Gallon Tanker

○ International Chassis

○ Camions Helie Fire Body

NEW ALUMINUM TANK 5454-H32 IS  
LIFETIME WARRANTY  
(5) YEARS ON EMERGENCY LIGHTING  
(1) YEAR ON POWERTRAIN

Aluminum vs Poly (lifetime warranty) is:

- 2.98 times more dense (g/cm<sup>2</sup>)
- 62.72 times more elastic (GPA)
- 3.92 times more resistant to high temperature (° C)
- 20.83 times more rigid versus its weight (MN-m/kg)
- 2.12 times more strong versus its weight (kN-m/kg)
- 20.0 less fragile times at -40 ° F and +.
- 1.55 times faster unloading.
- 9.75 times more resistant to pressure from loading
- 6.30 times more elastic (MPa)
- Much safer thanks to its centre of gravity very low more easy maintenance.
- Much easier to repair and maintain.
- Tensile strength of polypropylene is 4,500 psi
- Tensile strength of aluminium is 44,000 psi

○ Navistar 285 HP Diesel Engine

○ Allison Automatic Transmission

○ 2000 Gallon Tank

○ Mileage: 98,000

○ Additional equipment not included with purchase unless otherwise listed. Mileage readings may not be real-time and should be confirmed.

○ Our tanks are specially designed for Fire Services and designed to meet NFPA and ULC standards. Our semi-elliptical tanks provide the lowest possible center of gravity in accordance with DOT406, CAN / ULC S-515-04, NFPA

In 20 years, no (0%) claim and (0%) repair on our tanks delivered demonstrating the superiority of the product without any hesitation.

- HELIE FIRE BODY

- CHASSIS SPECIFICATIONS :

- 2012 INTERNATIONAL

DT 285HP

14,000 Front axle

23,000 Rear axle

ALLISON 3500 RDS AUTOMATIC

TRANSMISSION

FULL LOCK

AIR RIDE

158,000 KILOS (98,000 MILES)

ALUMINUM WHEELS

NEW ALUMINUM TANK 5454-H32 IS  
LIFETIME WARRANTY  
(5) YEARS ON EMERGENCY LIGHTING  
(1) YEAR ON POWERTRAIN

INTERNATIONAL DEALER FULL  
INSPECTION BEFORE DELIVERY  
GOVERNMENT TRUCK INSPECTION  
BEFORE DELIVERY  
PERFORMANCE TESTS BEFORE  
DELIVERY

NFPA/ULC Longitudinal and transverse  
baffles

Tank compartments dimensions : Door  
facing upwards 60 "long 38 "high, 28"  
deep, 30 degree rear

Two (2) drain installed in the front  
Filling 10 "cover installed on the top of the  
tank  
Manhole cover: 20 "

One (1) 10 " discharge valve with actuator  
One (1) 26 " discharge extension -  
One (1) 90 degrees elbow for side dump

One (1) 4 " Pre-connect (inlet/outlet) driver

side tank compartment  
One (1) valve 1/4 "to eliminate pressure

One (1) 4 " Inlet at the rear passenger side  
-  
One (1) valve 1/4 "to eliminate pressure

One (1) tank 4 " victaulic with mesh and  
plug drain  
One (1) overflow 6 "pipe with box on top of  
the tank

#### LIGHTING PACKAGE :

- (1) Whelen Justice light bar 62"
- (1) Tecniq perimeter light
- (2) Whelen Strobe L31HRF
- (2) Whelen Strobe
- (2) Whelen Scene light Series 900
- (8) Whelen Interception light Series 600
- (11) Work light
- LED lighting in tank compartments
- Witness light for door open
- Whelen Siren/speaker
- Whelen console
- Back up camera with 7" screen color/sound

#### EQUIPMENT :

- 2000 Gallon Rol-La-Tank (Dump tank)
- PFP-38hpKHL-2D PUMP
- (2) Rear compartments
- Pike poles holders
- Ladder rack holder
- (1) Anode (protect the tank)
- (2) Hooks front
- (2) Hooks rear
- (2) Water indicator (1) Back – (1) Inside cab
- (3) Hose suctions holders
- Kussmaul Auto eject & Air eject
- Sliding drawer
- Heater in pump compartment
- Battery charger + 120V Power outlet
- Automatic dump discharge system
- (3) Flares
- Road triangles
- Extinguisher

#### LETTERING :

- 3M Reflective lettering (Fire department lettering)
- Rear back chevron
- Rear bumper with chevron

Aluminum vs Poly (lifetime warranty) is:

- 2.98 times more dense (g/cm<sup>2</sup>)
- 62.72 times more elastic (GPA)
- 3.92 times more resistant to high temperature (° C)
- 20.83 times more rigid versus its weight (MN-m/kg)
- 2.12 times more strong versus its weight (kN-m/kg)
- 20.0 less fragile times at-40 ° F and +.
- 1.55 times faster unloading.
- 9.75 times more resistant to pressure from loading
- 6.30 times more elastic (MPa)
- Much safer thanks to its centre of gravity very low more easy maintenance.
- Much easier to repair and maintain.
- Tensile strength of polypropylene is 4,500 psi
- Tensile strength of aluminium is 44,000 psi



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at [www.firetruckmall.com](http://www.firetruckmall.com)