BRINDLEE MOUNTAIN



Contact Us

Office: 256.776.7786

Email: sales@firetruckmall.com Website: www.firetruckmall.com

15410 US Highway 231, Union Grove, AL 35175

Stock #: 18672

Price: Sold and Delivered

2007 Osco Peterbilt Commercial Elliptical Tandem-Axle Tanker

 2007 Osco Peterbilt Commercial Elliptical Tandem-Axle Tanker 	O Peterbilt Chassis	O Paccar PX-8 300 HP Diesel Engine
○ Allison 3000 RDS Automatic Transmission	 Berkeley B3Z PTO Driven Centrifugal 750 GPM Pump 	→ 3000 Gallon Polypropylene Tank

O Mileage: 201,000

Standard Features:

3/4" and 1/2" Polypropylene construction

Primed and painted finish to match the chassis

6" Internal Vent

Scene light and beacon light brackets

Polypropylene conduit for wires

Hot Dip Galvanized Sub-frame

All tanks are spring mounted to chassis in the front and middle and solid mounted in rear

TANK OPENINGS:

- (1) 3" opening in rear street side of tank - Valve and male NST fitting on rear of tank – 2.5"
- (1) 3" opening in rear curb side of tank Valve and male NST fitting on rear of tank 2.5"
- (1) 4" box sump located front bottom center to supply pump with 4" Air operated valve

DUMP VALVE:

(1) 10" Newton dump valve on rear – Mild steel painted with electric actuation

WATER PUMP SYSTEM:

Berkeley B3Z PTO driven centrifugal pump

750 GPM Max Discharge

70 PSI Max Pressure

1 - 2.5" 1 - 2.5" discharge ischarge on driveron side passenger between side cab and between tank cab and with tank valve with and 2.5" valve fitting and 2.5" fitting

- (1) 2" Pump recirculation / tank fill line
- (1) 1.5" Aquatrol relief valve to drain to the ground Set at 100 PSI

Pump Suction:

- (1) 3" Suction Line on driver side of tank
- (1) 3" Suction Line on passenger side of tank
- (1) Trident Air Primer
- (1) Whelen ITL-40 Electronic water level gauge on pump panel
- (1) Whelen PSTANK Electronic water level gauge on rear of tank

All mild Small steel Aluminum plumbingpump and panel on manifoldstriver side above catwalk

 Additional equipment not included with purchase unless otherwise listed. Mileage readings may not be real-time and should be confirmed. O GVWR: 52,000

APPARATUS BODY ACCESSORIES:

Two (2) Aluminum catwalks, one each side

Two (2) Aluminum diamond tread storage compartments

Aluminum swing-open doors on each compartment

48" x 24" x 24" Compartment on driver side

48" x 24" x 24" Compartment on passenger side

LED interior compartment lights

Sweep-out floors

One (1) aluminum hose tray on driver side catwalk

One (1) manual swing down porta-tank rack on passenger side

Built to fit 3000 gallon "Fol-da-tank"

Aluminum diamond tread cover

CHASSIS:

2007 Peterbilt 340 tandem axle (201,000 miles)

Color: Yellow (Original paint)

Motor: PACCAR PX8 (Cummins

ISC) 300 Hp

Transmission: Allison Automatic

3000 RDS transmission

Aluminum wheels on front axle

Aluminum wheels on rear axle

11R x 22.5 Tires on front axles

11R x 22.5 tires on rear axles

12,000# front axle capacity

40,000# rear axle capacity

Air ride suspension

Inter-axle Differential Lock

Air conditioning

AM/FM Radio

Air ride driver side seat

Stationary passenger side seat

Tow hooks front and rear – Recessed hooks on rear

Master battery disconnect

Air horns underneath cab to leave room for light bar

MISCELLANEOUS ITEMS:

4" Reflective stripping on each side of apparatus

Chevron Striping on rear

Alternating 6" RED/LIME YELLOW High Intensity reflective tape



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at www.firetruckmall.com