



2009 GMC Tanker

Contact Us

Office : 256.776.7786
Email : sales@firetruckmall.com
Website: www.firetruckmall.com

15410 US Highway 231,
Union Grove, AL 35175
Stock #: 08612
Price: Sold and Delivered

☐ 2009 GMC Tanker

☐ T-8500 GMC Chassis

☐ Camions Helie Fire Body

Offering installation service of a brand new
1500 to 2500 gallon tank with firefighter
pack on this chassis!

NO Miles (brand new chassis)

☐ Diesel Engine

☐ Automatic Transmission

☐ 1500 to 2500 Gallon Tank

- Available with portative pump or PTO
 - (6) Whelen Interception Series 600
 - (2) Whelen LINZ6FC
 - (2) Whelen Series 900
 - (9) Work light LED
 - (2) Beacon
 - (1) Justice light bar 62"
 - LED lighting in compartments

Universal Threads

- Additional equipment not included with purchase unless otherwise listed.

- Rear View with 7 " colour screen camera & sound

- Reflective Strips
- Rear Chevrons
- Pare shock ultra rugged, reflective & nonslip
- Rear scale nonslip
- (1) Anode
- (2) Hooks Front
- (2) Hooks Rear
- (3) Hose suction holders
- (2) Water indicators
- Kussmaul Auto eject & air eject
- (3) Flares
- Road Triangles
- Extinguisher
- Sliding drawer
- Heating in pump compartment
- Input for portable pump
- Battery charger
- Shelf can be added in compartment

Longitudinal baffle

Two (2) drain installed in the front

Manhole cover: 20 "

Filling 10 "cover installed in the center of the tank

One (1) exit 10 "with the rear butterfly valve and actuator -One (1) adapter right 26 " -

One (1) adapter with elbow 90 degree

One (1) output 4 "STORZ with valve trunk driver side

-One (1) valve 1/4 "to eliminate pressure

One (1) entry 4 "STORZ at the rear passenger side -

One (1) valve 1/4 "to eliminate pressure

One (1) tank 4 " victaulic with mesh and plug drain

One (1) overflow 6 "pipe with box on top of the tank Safes: Welded-side driver with 1 "recoil

Door facing upwards 60 "long 38 "high, 28" deep, 30 degree rear

Aluminum vs Poly (lifetime warranty) is:

- 2.98 times more dense (g/cm²)
- 62.72 times more elastic (GPA)
- 3.92 times more resistant to high temperature (° C)
- 20.83 times more rigid versus its weight (MN-m/kg)
- 2.12 times more strong versus its weight (kN-m/kg)
- 20.0 less fragile times at-40 ° F and +.
- 1.55 times faster unloading.
- 9.75 times more resistant to pressure

from loading

- 6.30 times more elastic (MPa)
- Much safer thanks to its centre of gravity very low more easy maintenance.
- Much easier to repair and maintain.
- Tensile strength of polypropylene is 4,500 psi
- Tensile strength of aluminium is 44,000 psi



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at www.firetruckmall.com