



## Contact Us

Office : 256.776.7786  
Email : [sales@firetruckmall.com](mailto:sales@firetruckmall.com)  
Website: [www.firetruckmall.com](http://www.firetruckmall.com)

15410 US Highway 231,  
Union Grove, AL 35175  
Stock #: 08760  
Price: No Longer Available

2018 Helie Freightliner 2000 Gallon Tanker

○ 2018 Helie Freightliner 2000 Gallon Tanker ○ M2-106 Freightliner Chassis

○ Camions Helie Fire Body

NEW ALUMINUM TANK 5454-H32 IS  
LIFETIME WARRANTY  
(5) YEARS ON EMERGENCY LIGHTING  
FREIGHTLINER MEDIUM TRUCK  
WARRANTY

INTERNATIONAL DEALER FULL  
INSPECTION BEFORE DELIVERY  
GOVERNMENT TRUCK INSPECTION  
BEFORE DELIVERY  
PERFORMANCE TESTS BEFORE  
DELIVERY

NFPA/ULC Longitudinal and transverse  
baffles

- DIFFERENTIAL LOCK
- AIR RIDE
- FULL CHROME ACCESSORIES
- PTO PROVISION

○ Cummins 325 HP Diesel Engine

○ Allison 3000EVS Automatic Transmission

○ 2000 Gallon Aluminum Tank

- Tank compartments dimensions : Door facing upwards 60 "long 38 "high, 28" deep, 30 degree rear
- Additional equipment not included with purchase unless otherwise listed.

Two (2) drain installed in the front  
 Filling 10 "cover installed on the top of the tank  
 Manhole cover: 20 "

One (1) 10 " discharge valve with actuator  
 ↳One (1) 26 " discharge extension ↳  
 One (1) 90 degrees elbow for side dump

One (1) 4 " Pre-connect (inlet/outlet) driver side tank compartment  
 ↳One (1) valve 1/4 "to eliminate pressure

One (1) 4 " Inlet at the rear passenger side ↳  
 One (1) valve 1/4 "to eliminate pressure

One (1) tank 4 " victaulic with mesh and plug drain  
 One (1) overflow 6 "pipe with box on top of the tank

Aluminum vs Poly (lifetime warranty) is:

- 2.98 times more dense (g/cm<sup>2</sup>)
- 62.72 times more elastic (GPA)
- 3.92 times more resistant to high temperature (° C)
- 20.83 times more rigid versus its weight (MN·m/kg)
- 2.12 times more strong versus its weight (kN·m/kg)
- 20.0 less fragile times at -40 ° F and +.
- 1.55 times faster unloading.
- 9.75 times more resistant to pressure from loading
- 6.30 times more elastic (MPa)
- Much safer thanks to its centre of gravity very low more easy maintenance.
- Much easier to repair and maintain.
- Tensile strength of polypropylene is 4,500 psi
- Tensile strength of aluminium is 44,000 psi

- • DIFFERENTIAL LOCK
- AIR RIDE
- FULL CHROME ACCESSORIES
- PTO PROVISION

#### EQUIPMENT :

- (1) Anode (protect the tank)
- (2) Hooks front
- (2) Hooks rear
- (2) Water indicator (1) Back – (1)

#### Inside cab or near pump

- (3) Hose suction holders
- Kussmaul Auto eject & Air eject
- Sliding drawer
- Heater in pump compartment
- Battery charger + 120V Power outlet
- Automatic dump discharge system
- (3) Flares
- Road triangles
- Extinguisher

#### LETTERING :

- 3M Reflective lettering (Fire department lettering)
- Rear back chevron
- Rear bumper with chevron



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at [www.firetruckmall.com](http://www.firetruckmall.com)