

## Contact Us

Office: 256.776.7786

Email: sales@firetruckmall.com Website: www.firetruckmall.com

15410 US Highway 231, Union Grove, AL 35175

Stock #: 08807

Price: Sold and Delivered

## Kohler 38HP Gas Powered Pump

O Kohler 38HP Gas Powered Pump

O etc. Chassis

- O PUMP UNIT SPECIFICATIONS
  - C.E.T. is using the new technology of a dual stage centrifugal pump.
  - Pump body made from resistant aluminum alloy.
  - · Bronze impellers.
  - · Mechanical shaft seal.
  - · Stainless steel pump shaft.
  - Exhaust priming system, guaranteed up to 20' (6 meter) lift.
  - Two 2 1/2" (65 mm) delivery outlets. One 4" (100 mm) suction inlet.
  - Dimensions: Length: 37" (940 mm);
     Width: 26" (660 mm); Height: 31" (787 mm)
  - Weight: 275 lbs (125 kg).

## O CONTROL PANEL

- Engine start/stop button.
- Throttle control lever.
- · Choke control lever.
- · Oil control lamp.
- · Operating panel light.
- · Pressure gauge.
- Vacuum pressure gauge.

## PERFORMANCE

600 GPM (2268 LPM) @ 25 PSI (1.7 bar)
480 GPM (1814 LPM) @ 50 PSI (3.5 bar)
375 GPM (1718 LPM) @ 75 PSI (5.2 bar)
300 GPM (1134 LPM) @ 100 PSI (6.9 bar)
140 GPM (529 LPM) @ 150 PSI (10.3 bar)

- O ENGINE SPECIFICATIONS
  - Kohler 38hp at 3600 RPM, air cooled engine.
  - 3-cylinder, 4-stroke gasoline engine.
  - 12V electric start.
  - 6 gallon (22 I) capacity fuel tank.
- Additional equipment not included with purchase unless otherwise listed.

O YOUR PUMP COMES WITH A LIMITED 3
YEAR WARRANTY AND A FULL
WARRANTY ON ALL MECHANICAL
COMPONENTS



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at www.firetruckmall.com