BRINDLEE MOUNTAIN



Honda 6.5HP Goliath Gas Powered Pump

O Honda 6.5HP Goliath Gas Powered Pump O etc. Chassis

Contact Us

Office : 256.776.7786 Email : sales@firetruckmall.com Website: www.firetruckmall.com

15410 US Highway 231, Union Grove, AL 35175 Stock #: 08864 Price: Sold and Delivered

O ENGINE SPECIFICATIONS

• Honda 6.5hp at 3600 RPM GX200, air cooled engine.

- Single cylinder gasoline engine.
- Manual recoil start.
- 1.5 gallon (5.7 l) integrated fuel tank.
- Additional equipment not included with purchase unless otherwise listed. Mileage readings may not be real-time and should be confirmed.

O PUMP UNIT SPECIFICATIONS

- C.E.T. dual stage centrifugal pump.
- Pump body made from aluminum.

• Aluminum impeller. • Mechanical shaft seal.

- · Self-priming system.
- Two 1" (25 mm) delivery outlets and one
- 1 1/2" (38mm) NPSH delivery outlet.
- One 1 1/2" (38 mm) NPSH suction inlet.

• Dimensions (approx.) : Length : 19" (483 mm); Width : 17" (406 mm); Height : 16" (381 mm).

• Weight (approx.) : 59 lbs (27 kg).

• Your pump comes with a 3 year limited warranty & full year warranty on all mechanical components.



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at www.firetruckmall.com

Low oil alert.

O INCLUDED ACCESSORIES

PERFORMANCE

70 GPM (265 LPM) @ 10 PSI (0.7 bar) 40 GPM (151 LPM) @ 100 PSI (6.9 bar) 20 GPM (76 LPM) @ 125 PSI (8.6 bar)