Brindlee Mountain



Contact Us

Office: 256.776.7786

Email: sales@firetruckmall.com Website: www.firetruckmall.com

15410 US Highway 231, Union Grove, AL 35175

Stock #: 08192

Price: Sold and Delivered

Enforcer 60 Gallon Fire Extinguisher

O Enforcer 60 Gallon Fire Extinguisher

O etc. Chassis

Performance

Pressure Vessel Capacity: 60 U.S Gallons Finished Foam Capacity: Up to 600 U.S.

Gallons Finished Foam

Throw Distance: Up to 95 Feet

Discharge Duration: Up to 4 ½ Minutes General Specifications – Standards Pressure Vessel Construction: Carbon Steel to ASME Code Pressure Vessel

Dimensions: 20"x48" Fill Tower: 1 ½"

System Hoses: 3000psi Hard Rubber Hose Plumbing: All Stainless Steel With Brass

Fill Cap

Discharge Hose: 50' Lay Flat Hose

Hose Storage: Hose Tray

Propellant Type: Nitrogen or Compressed

Air

Propellant Cylinder Capacity: Two 90 Cubic Foot Cylinders Propellant Cylinder Brackets: 3/8" Steel Placed in Frame Walls

Discharge Nozzle: 1" Pistol Grip Discharge Nozzle Tip: Power Tip

Technology

Wheels: 15.5" Flat Free Wheels

Dimensions Height: 38.5" Depth: 42" Length: 54.5"

Empty Weight: 485 Pounds Loaded Weight: 985 Pounds • Additional equipment not included with purchase unless otherwise listed.



feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at www.firetruckmall.com