BRINDLEE MOUNTAIN



Vanguard 18HP Gas Powered Pump

○ Vanguard 18HP Gas Powered Pump

O ENGINE SPECIFICATIONS

- Honda 20hp at 3600 RPM, air cooled engine.
- V-Twin cylinder gasoline engine.
- · Electric start.
- 6 gallon (22 l) detachable fuel tank.

O etc. Chassis

O PUMP UNIT SPECIFICATIONS

- C.E.T. single stage centrifugal pump.Pump body made from high resistant
- aluminum alloy.
- Bronze impeller.
- Mechanical shaft seal.
- Exhaust priming system, guaranteed up to 20' (6 meter) lift.
- One 2 1/2" (65 mm) delivery outlet with 1/4-turn ball valve.
- One 4 " (100 mm) suction inlet.

DIMENSIONS

Length : 25 7/8" (650 mm); Width : 20 1/4 " (514 mm); Height : 22 1/8" (561 mm). Weight : 185 lbs (84 kg). O Gas Engine

0

Contact Us

Office: 256.776.7786

15410 US Highway 231,

Union Grove, AL 35175

Price: Sold and Delivered

Stock #: 08912

Email : sales@firetruckmall.com

Website: www.firetruckmall.com

INCLUDED ACCESSORIES

- · Swivel spotlight.
- 36 watts alternator.
- · Low oil alert.
- Pressure gauge.
- 12-V battery.

PERFORMANCE

510 GPM (1928 LPM) @ 10 PSI (0.7 bar) 410 GPM (1550 LPM) @ 25 PSI (1.7 bar) 315 GPM (1191 LPM) @ 50 PSI (3.5 bar) 190 GPM (718 LPM) @ 75 PSI (5.2 bar) 75 GPM (284 LPM) @ 100 PSI (6.9 bar)

- Additional equipment not included with purchase unless otherwise listed.
- Your pump comes with a 3 year limited warranty & full year warranty on all mechanical components.



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at www.firetruckmall.com