BRINDLEE MOUNTAIN



Contact Us

Office: 256.776.7786

Email: sales@firetruckmall.com Website: www.firetruckmall.com

15410 US Highway 231, Union Grove, AL 35175

Stock #: 08919

Price: Sold and Delivered

Honda 20HP Gas Powered Pump

- O Honda 20HP Gas Powered Pump
- O ENGINE SPECIFICATIONS
 - Honda 20hp at 3600 RPM, air cooled engine
 - V-Twin cylinder gasoline engine.
 - 12V Electric start.
 - 6 gallon (22 l) detachable fuel tank. The fuel tank is made from plastic.

- O etc. Chassis
- O PUMP UNIT SPECIFICATIONS
 - Transmission drive C.E.T. single stage centrifugal pump.
 - Pump body made from high resistant aluminum alloy.
 - · Bronze impeller.
 - · Mechanical shaft seal.
 - · Stainless steel pump shaft.
 - · Belt drive transmission.
 - Exhaust priming system, guaranteed up to 15' (4.5 meter) lift.
 - One 1 1/2" (38 mm) delivery outlet with 1/4-turn ball valve.
 - One 2 1/2 " (65 mm) suction inlet.

DIMENSIONS

Length: 21 1/4" (539 mm); Width: 27" (585 mm); Height: 20 7/8" (530 mm). Weight: 175 lbs (80 kg).

 Additional equipment not included with purchase unless otherwise listed. Your pump comes with a 3 year limited warranty & full year warranty on all mechanical components. Gas Engine

0

INCLUDED ACCESSORIES

- 36 watt alternator.
- · Low oil alert.
- · Pressure gauge.
- 12-V battery.

PERFORMANCE

150 GPM (567 LPM) @ 50 PSI (3.5 bar)

110 GPM (416 LPM) @ 100 PSI (6.9 bar)

70 GPM (265 LPM) @ 150 PSI (10.3

45 GPM (170 LPM) @ 200 PSI (13.8

45 G bar)

5 GPM (19 LPM) @ 250 PSI (17.2

bar)



Brindlee Mountain Fire Apparatus is one of the world's largest used fire truck sales and service companies. Based just outside of Huntsville, Alabama, the company has forty-five full-time personnel occupying over 12,000 square feet. Our mechanics, all of whom are EVT certified, perform pump tests, general repairs, preventative maintenance, and body, collision, and paint work on over 500 used fire trucks every year. Visit us online at www.firetruckmall.com