



Contact Us

Office : 256.776.7786
Email : sales@firetruckmall.com
Website: www.firetruckmall.com

15410 US Highway 231,
Union Grove, AL 35175
Stock #: 08931
Price: Sold and Delivered

PFP-25HP-DSL

DIESEL POWERED PUMP

This high pressure/high volume pump is made to fight fires or supply water to the fire scene. The engine and pump are mounted on a steel protective frame with folding handles.

Also available in skid version



Kubota 25HP Diesel Powered Pump

○ Kubota 25HP Diesel Powered Pump

○ ENGINE SPECIFICATIONS

- Kubota 25hp at 3600 RPM, water cooled engine.
- 3-cylinder diesel engine
- Electric start.
- 6 gallon (22 l) detachable fuel tank.

○ etc. Chassis

○ PUMP UNIT SPECIFICATIONS

- C.E.T. two stage centrifugal pump.
- Pump body made from high resistant aluminum alloy.
- Bronze impellers.
- Mechanical shaft seal.
- Stainless steel pump shaft.
- Electric priming system, guaranteed up to 20' (6 meter) lift.
- Two 2 ½" (65 mm) delivery outlets
- One 4" (100 mm) suction inlet.

DIMENSIONS

Length : 40 ¼" (1022 mm);
Width : 26" (660 mm);
Height : 34 ¼" (870 mm).
Weight : 350 lbs (134 kg).

○ Diesel Engine

○

CONTROL PANEL

- Engine start/stop switch.
- Throttle control lever.
- Operating panel light.
- Pilot lights.
- Pressure gauge.
- Vacuum pressure gauge.

PERFORMANCE

465 GPM (1760 LPM) @ 10 PSI (0.7 bar)
425 GPM (1608 LPM) @ 25 PSI (1.7 bar)
325 GPM (1230 LPM) @ 50 PSI (3.5 bar)
200 GPM (757 LPM) @ 100 PSI (6.9 bar)
100 GPM (378 LPM) @ 125 PSI (8.6 bar)
30 GPM (113 LPM) @ 150 PSI (10.3 bar)

○ Additional equipment not included with purchase unless otherwise listed. Mileage readings may not be real-time and should be confirmed.

○ Your pump comes with a 3 year limited warranty & full year warranty on all mechanical components.

